

Concrete slab

Rigid WB6M hanger folded & fixed to concrete slab at 600mm ctrs using 1/M8 Hilti HUS-3 anchor, 55mm embedment.

Ribon EB3M at 900mm ctrs

**DESIGN WIND LOADINGS:
RIBON PANEL STRUCTURAL
REQUIREMENT/
8G 17mm wafer head self drilling
screw fixed at each panel/bracket
connection.**

150mm Max.

Rigid longitudinal brace fixed using M8 Hilti HUS-3 x 55mm to concrete slab. 2/10g Tek screws to hanger at bottom. (refer to bracing schedule for locations).

0.55 BMT RIBON PANEL

D-39A

SUSPENDED SOFFIT- SIDE ELEVATION

1:10

Issue: OCT 2020

Ribon Ltd

P.O.Box 315-555
Silverdale, Auckland, 0932

Ph: 022 641 0942
E: keith.russell@ribon.co.nz
E: jessica@ribon.co.nz
W: www.ribon.co.nz



RIBON[®]

Drawing Name

Sheet

Scale

Notes:

1. Contractor to check all dimensions and conditions on site before commencing work.
2. In the event of a discrepancy consult the designer.
3. Reproduction of any plans for any other purpose, without permission of Ribon Ltd is strictly prohibited.